



उप.सं. ३२

माडी नगरपालिका

नगर कार्यपालिकाको कार्यालय



बसन्तपुर, धितवन
सुनसरी प्रदेश, नेपाल

फोन : ०३१-५०१०२१

दिनांक २०७३-०३-१४

विषय: बजार दररेट उपलब्ध गराईदिने सम्बन्धमा ।

दोस्रो पटक प्रकाशित सूचना !!!

श्री सबै फर्म तथा कम्पनीहरु,

.....

प्रस्तुत विषयमा यस कार्यालयका लागि यसैसाथ संलग्न विवरण तथा स्पेशिफिकेशन बमोजिमको सि.सि.क्यामेराको बजार दररेट आवश्यक परेको हुँदा यो सूचना प्रकाशन भएको मितिले (सात) दिन भित्र यस कार्यालयमा बजार दररेट पेश गर्नुहुन अनुरोध छ।

प्रमुख प्रशासकीय अधिकृत
प्रमुख प्रशासकीय अधिकृत

**Madi Municipality
Office Of Municipal Executives
Basantapur, Chitwan**



CCTV Surveillance System Specification – Ward No. 9 Office, Krishnanagar BHC, Agri Service centre & Surrounding Area

Fiscal Year: 083/84

S.N.	Equipment	Minimum Specification	Qty.	Remarks
1	16-Channel NVR	16 Channel Network Video Recorder; H.265/H.265+ compression; minimum 4MP recording support; HDMI/VGA output; 16 IP camera support; remote monitoring via mobile/web; HDD support for surveillance-grade storage; ONVIF compatible	1 Set	
2	4MP IP PoE Camera	4MP (2560×1440) resolution; IP camera; PoE (802.3af/at) support; IR Night Vision minimum 30m; 2.8mm/4mm fixed lens; Day/Night function; DWDR; 3D DNR; Motion Detection; H.265/H.265+; IP66 weatherproof; suitable for indoor/outdoor installation; ONVIF compatible	12 Nos.	
3	16-Port PoE Switch	16 × 10/100/1000 Mbps PoE ports; IEEE 802.3af/at compliant; Gigabit uplink ports; total adequate PoE power budget for connected cameras; unmanaged Plug & Play type; surge/overload protection	1 Set	
4	16TB Surveillance HDD	16TB capacity; 24×7 surveillance-grade operation; SATA interface; suitable for continuous CCTV recording; minimum 5400 RPM or equivalent; compatible with selected NVR	1 No.	
5	Cat6 UTP Cable	CAT6 UTP 4-pair network cable; 23/24 AWG; 305m box/roll; 100% copper conductor; suitable for Gigabit Ethernet and PoE CCTV installation	2 Roll	
6	RJ45 Connectors & Accessories	CAT6 compatible RJ45 connectors, boots, junction/termination accessories and required consumables	1 Lot	
7	LED Monitor	Minimum 21.5" Full HD (1920×1080); HDMI/VGA input; suitable for continuous CCTV monitoring; LED display	1 No.	
8	Installation & Configuration	Camera mounting, Cat6 cabling, termination, NVR and PoE switch configuration, camera addressing, recording configuration, date/time setting, remote/mobile viewing configuration, testing and commissioning	1 Lot	

Prepared By
Prabin Bhandari
IT Officer

Checked By
Nabin Raj Ruwali
Senior Section Officer

Approved By
Ramchandra Khadka
Acting CAO

Acting Chief Administrative Officer